

AMI Graphical Bios Setup 1994 American Megatrends

<TAB> Move among windows
<ENTER> Select
<ESC> Previous Level
<Alt+H> Help
<Alt+Space bar> Global Exit Choices: Save changes and exit (Default), Do Not Save and exit, or Continue.

SETUP

Standard

Date/Time Use +/- to adjust, arrow keys to move
Floppy Drive A **Not Installed**
Floppy Drive B **1.44 MB 3.5"**
Master Disk Type: **USER**
 Cyl: **2099**
 Hd: **16**
 WP: **0**
 LZ: **2099**
 Sec: **63**
 Size(MB): **1033 MB**
Slave Disk Not Installed

Advanced

Typematic Rate (Chars/Sec)	30
System Keyboard	Present
Primary Display	VGA/EGA
Above 1 MB Memory Test	Enabled
Memory Test Tick Sound	Enabled
Hit "Del" Message Display	Enabled
Extended BIOS RAM Area	0:300
Wait For "F1" If Any Error	Enabled
System Bootup Num Lock	Off
Numeric processor test	Enable
Floppy Drive Seek at Boot	Disabled
System Boot Up Sequence	C:, A:
Password Checking	Setup
Video Shadow, C000,32K	Enabled
Shadow C800,32K	Disabled
Shadow D000,32K	Disabled
Shadow D800,32K	Disabled
Shadow E000,32K	Disabled
Shadow E800,32K	Disabled
Internal Cache	Enabled
Internal Cache, write mode	Wr-back
External Cache	Enabled
External Cache write mode	WR-Back
Video Rom Cash C000, 32K	Enabled
System Rom Cash F000, 64K	Enabled
Non-Cashable #1 Size	Disabled
Non-Cashable #2 Size	Disabled
IDE Block Mode	Disabled
Primary IDE Auto Detection	Disabled
Primary Master IDE LBA Mode	Disabled
Primary Slave IDE LBA Mode	Disabled
Secondary IDE Drives Present	None

Chipset

Auto Config Function	Disabled
Bus Frequency	Clk /3
System Dram Speed	Slowest
Cache Burst Read Cycle time	2T
Cache Write Cycle Time	3T
Hidden Refresh	Enabled

<AMI-WINBIOS #2.WPD>