

Award Bios Setup (2A59GF2A) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User							
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None
 Drive B : 1.44M, 3.5 in.
 Floppy 3 Mode Support : Disabled
 Video : EGA/VGA
 Halt On : All Errors

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CFFFF Shadow	: Disabled
External Cache	: Enabled	D0000-D7FFF Shadow	: Disabled
Quick Power On Self Test	: Disabled	D8000-DFFFF Shadow	: Disabled
Boot Sequence	: C, A	E0000-E7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	E8000-EFFFF Shadow	: Disabled
Boot up Floppy Drive	: Disabled	PS/2 Mouse Function Ctrl	: Disabled
Boot up NumLock Status	: On	OS Select for DRAM >64MB	: Non-OS2
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Rate (Msec)	: 250		
Security Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		

CHIPSET FEATURES SETUP

Auto Configuration	: Disable
DRAM RAS# Prechage Time	: Fastest
DRAM R/W Leadoff Timing	: 6
Fast RAS to CAS Delay	: 3
DRAM Read Burst (EDO/FP)	: x222/x333
DRAM Write Burst Timing	: x333
Fast MA to RAS# Delay CLK	: 1
Fast EDO Path Select	: Disabled
Refresh RAS# Assertion	: 4 CLKS
ISA Bus Clock	: PCICLK/4
System BIOS Cacheable	: Disabled
Video BIOS Cacheable	: Enabled
8 Bit I/O Recovery Time	: 1
16 Bit I/O Recovery Time	: 1
Memory Hole at 15M-16M	: Disabled
Peer Concurrncy	: Enabled
Passive Release	: Enabled
Delayed Transaction	: Disabled

PNP/PCI Configuration

Resources Controlled By : Auto

Integrated Peripherals

IDE HDD Block Mode	: Disabled
PCI Slot IDE 2 nd Channel	: Disabled
On-Chip Primary PCI IDE	: Enabled
On-Chip Secondary PCI IDE	: Disabled
IDE Primary Master PIO	: Auto
IDE Primary Slave PIO	: Auto
OnBoard FDD Controller	: Enabled
OnBoard Serial Port 1	: 3F8/IRQ4
OnBoard Serial Port 2	: Disabled
OnBoard Parallel Port	: 378/IRQ7
OnBoard parallel Mode	: Normal
USB Controller	: Disabled