

## Award Bios Setup (2A4IBF2H)

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: Auto	0	0	0	0	0	0	Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None  
Drive B : 1.44M, 3.5 in.  
Video : EGA/VGA  
Halt On : All Errors

## BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CFFFF Shadow	: Disabled
External Cache	: Enabled	D0000-D7FFF Shadow	: Disabled
Quick Power On Self Test	: Disabled	D8000-DFFFF Shadow	: Disabled
Boot Sequence	: C, A		
Swap Floppy Drive	: Disabled		
Boot Up Floppy Seek	: Disabled		
Boot Up NumLock Status	: On		
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay ( Msec)	: 250		
Password Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		

## CHIPSET FEATURES SETUP

Auto Configuration	: Disabled	Onboard 496B IDE Port	: Both
ISA Bus Clock	: 1/4 PCLK	IDE 0 Master Mode	: Auto
Cache Write Cycle	: 2 CCLK	IDE 0 Slave Mode	: Auto
Cache Burst Read Cycle	: 1 CCLK	IDE 1 Master Mode	: Auto
L2 Cache/DRAM Cycle WS	: 2 CCLK	IDE 1 Slave Mode	: Auto
DRAM RAS to CAS Delay	: 3 CCLK	IDE Prefetch Read Buffer	: Both
DRAM Write Cycle	: 1 WS	IDE HDD Block Mode	: Disabled
DRAM Write CAS Pulse	: 1 CCLK	Onboard FDD Controller	: Enabled
DRAM CAS Precharge Time	: 1 CCLK	Onboard Serial Port 1	: COM1/3F8
DRAM RAS to MA Delay	: 2 CCLK	Onboard Serial Port 2	: Disabled
DRAM Speed	: Faster	Onboard Parallel Port	: 378H
DRAM Slow Refresh	: Disabled	Onboard Parallel Mode	: Normal
CPU Burst Write	: Disabled		
External Cache Policy	: Write Back		

## Power Management Setup

Power Management : Disabled  
All Others : Disregard

## PNP / PCI Configuration

PnP BIOS Configuration : Disabled