

Award Bios Setup (2A59Ht5A) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User	1083	2100	16	0	2100	63	Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None
Drive B : 1.44M, 3.5 in.
Video : EGA/VGA
Halt On : All Errors

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF Shadow	: Disabled
Quick Power On Self Test	: Disabled	D0000-D3FFF Shadow	: Disabled
Boot Sequence	: C, A	D4000-D7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	D8000-DBFFF Shadow	: Disabled
Boot up Floppy Seek	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up NumLock Status	: On		
Boot up System Speed	: High		
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay (Msec)	: 250		
Security Option	: Setup		

CHIPSET FEATURES SETUP

DRAM RAS# Precharge Time	: 4
DRAM R/W Leadoff Timing	: 7
Fast RAS To CAS Delay	: 3
DRAM Read Burst (EDO/FP)	: x444 / x444
DRAM Write Burst Timing	: x444
Fast MA to RAS# Delay Clk	: 2
Fast EDO Path Select	: Enabled
Refresh RAS# Assertion	: 5 CLKS
ISA Bus Clock	: PCICLK/4
System BIOS Cacheable	: Enabled
Video BIOS Cacheable	: Enabled
8 Bit I/O Recovery Time	: 2
16 Bit I/O Recovery Time	: 1
Peer Concurrency	: Enabled
Chipset NA# Asserted	: Enabled

Power Management Setup

Power Management	: Disabled
All Others	: Disregard

PNP / PCI Configuration

Resources Controlled By	: Auto	PCI IRQ Activated By	: Level
Reset Configuration Data	: Disabled	PCI IDE IRQ Map To	: ISA

Integrated Peripherals

IDE HDD Block Mode	: Disabled
IDE Primary Master PIO	: Auto
IDE Primary Slave PIO	: Auto
IDE Secondary Master PIO	: Auto
IDE Secondary Slave PIO	: Auto
On-Chip Primary PCI IDE	: Enabled
On-Chip Secondary PCI IDE	: Enabled
PCI Slot IDE 2ed Channel	: Enabled
USB Controller	: Disabled
OnBoard FDD Controller	: Enabled
OnBoard Serial Port 1	: Com1 / 3F8
OnBoard Serial Port 2	: Disabled
OnBoard Parallel Port	: 378H
OnBoard parallel Mode	: SPP