

Award Bios Setup (2A59FF2A) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User	2112	4092	16	0	4092	63	Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None
Drive B : 1.44M, 3.5 in.
Video : EGA/VGA
Halt On : All Errors

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF Shadow	: Disabled
Quick Power On Self Test	: Disabled	D0000-D3FFF Shadow	: Disabled
Boot Sequence	: C, A	D4000-D7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	D8000-DBFFF Shadow	: Disabled
Boot up Floppy Seek	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up NumLock Status	: On	PS/2 mouse function control	: Disabled
Gate A20 Option	: Fast	OS Select For DRAM> 64MB	: Non-OS2
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay (Msec)	: 250		
Security Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		

CHIPSET FEATURES SETUP

Auto Configuration	: Disabled	Chipset Special Features	: Enabled
DRAM RAS# Precharge Time	: 4	DRAM ECC/PARITY Select	: ECC
DRAM R/W Leadoff Timing	: 7/6	Memory Parity/ECC Check	: Auto
Fast RAS# To CAS# Delay	: 3	Single Bit Error Report	: Disabled
DRAM Read Burst (EDO/FP)	: x333 / x444	Passive Release	: Enabled
DRAM Write Burst Timing	: x333	Delayed Transaction	: Enabled
Turbo Read Leadoff	: Disabled		
DRAM Speculative Leadoff	: Disabled		
Turn-Around Insertion	: Disabled		
ISA Clock	: PCICLK/4		
System BIOS Cacheable	: Enabled		
Video BIOS Cacheable	: Enabled		
8 Bit I/O Recovery Time	: 1		
16 Bit I/O Recovery Time	: 1		
Memory Hole At 15M- 16M	: Disabled		
Peer Concurrency	: Enabled		

Power Management Setup

Power Management : Disabled
All Others : Disregard

PNP / PCI Configuration

Resources Controlled By	: Auto	PCI IRQ Activated By	: Level
Reset Configuration Data	: Disabled	PCI IDE IRQ Map To	: ISA
		Primary IDE INT#	: A
		Secondary IDE INT#	: B

Integrated Peripherals

IDE HDD Block Mode : Disabled
PCI Slot IDE 2nd Channel : Enabled
On-Chip Primary PCI IDE : Enabled
On-Chip Secondary PCI IDE : Disabled
IDE Primary Master PIO : Auto
IDE Primary Slave PIO : Auto
OnBoard FDD Controller : Enabled
OnBoard Serial Port 1 : 3F8/IRQ4
OnBoard Serial Port 2 : Disabled
OnBoard Parallel Port : 378/IRQ7
OnBoard parallel Mode : ECP/EPP
ECP Mode Use DMA : 3
USB Controller : Disabled