

### Award Bios Setup (2A59IT5A) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User	1704	3303	16	0	3303	63	Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None  
Drive B : 1.44M, 3.5 in.  
Floppy 3 Mode Support : Disabled  
Video : EGA/VGA  
Halt On : All Errors

### BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF Shadow	: Disabled
Quick Power On Self Test	: Enabled	D0000-D3FFF Shadow	: Disabled
Boot Sequence	: C only	D4000-D7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	D8000-DBFFF Shadow	: Disabled
Boot up Floppy Seek	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up Num Lock Status	: On		
Boot up System Speed	: High		
Typematic Rate Setting	: Enabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay ( Msec)	: 250		
Security Option	: Setup		
PS/2 Mouse Function Control	: Disabled		
PCI/VGA Palette Snoop	: Disabled		
Assign IRQ for VGA	: Enabled		
OS Select For DRAM > 64 MB	: Non-OS2		

### CHIPSET FEATURES SETUP

Auto Configuration	: Disabled	PCI Delayed Transaction	: Enabled
DRAM Leadoff Timing	: 11 / 7 / 4	Pipeline Cache Timing	: Faster
DRAM Read Burst (EDO/FP)	: x444 / x444	Chipset NA# Asserted	: Enabled
DRAM Write Burst Timing	: x444	Mem. Drive Str.(MA/RAS)	: Auto
Fast EDO Leadoff	: Disabled	DRAM Refresh Rate	: 15.6 us
Refresh RAS# Assertion	: 4 CLKS		
Fast RAS To CAS Delay	: 2		
DRAM Page Idle Timer	: 2 CLKS		
DRAM Enhanced Paging	: Enabled		
Fast MA to RAS # Delay	: 2 CLKS		
SDRAM (CAS Lat/RAS-to-CAS)	: 3/3		
SDRAM Speculative Read	: Disabled		
System BIOS Cacheable	: Enabled		
Video BIOS Cacheable	: Enabled		
8 Bit I/O Recovery Time	: 1		
16 Bit I/O Recovery Time	: 2		
Memory Hole at 15M-16M	: Enabled		
PCI 2.1 Compliance	: Enabled		
PCI Passive Release	: Enabled		

### PNP/PCI Configuration

PNP OS Installed	: No	PCI IDE IRQ Map2	: PCI Auto
Resources Controlled By	: Auto	Primary IDE INT #	: A
Reset Configuration Data	: Disabled	Secondary IDE INT #	: B

### Integrated Peripherals

IDE HDD Block Mode	: Disabled	OnBoard Parallel Port	: 378/IRQ7
IDE Primary Master PIO	: Auto	OnBoard parallel Mode	: Normal
IDE Primary Slave PIO	: Auto		
IDE Secondary Master PIO	: Auto		
IDE Secondary Slave PIO	: Auto		
IDE Primary Master UDMA	: Auto		
IDE Primary Slave UDMA	: Auto		
IDE Secondary Master UDMA	: Auto		
IDE Secondary Slave UDMA	: Auto		
On-Chip Primary PCI IDE	: Enabled		
On-Chip Secondary PCI IDE	: Enabled		
USB Latency Time(PCI CLK)	: 64		
USB Keyboard Support	: Disabled		
OnBoard FDC Controller	: Enabled		
OnBoard UART 1	: 3F8/IRQ4		
OnBoard UART 2	: Disabled		