

Award Bios Setup (2A59LDO0A) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: Auto	0	0	0	0	0	0	Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None
Drive B : 1.44M, 3.5 in.
Video : EGA/VGA
Halt On : All Errors

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF shadow	: Disabled
		D0000-D3FFF Shadow	: Disabled
Quick Power On Self Test	: Enabled	D4000-D7FFF Shadow	: Disabled
Boot Sequence	: C only	D8000-DBFFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up Floppy Drive	: Disabled		
Boot up Num Lock	: On		
Boot up System Speed	: High		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay (Msec)	: 250		
Security Option	: Setup		
IDE Seconf Channel Control	: Enabled		
PCI/VGA Palette Snoop	: Disabled		
OS Select For DRAM > 64 MB	: Non-OS2		
Report No FDD for WIN 95	: No		

CHIPSET FEATURES SETUP

DRAM Auto Configuration	: Disable	OnChip USB	: Disabled
DRAM Timing Control	: Normal		
Sustained 3T Write	: Disabled		
2 Bank PBSRAM	: 3-1-1-1		
Read Pipeline	: Enabled		
Write Pipeline	: Enabled		
Cache Timing	: Fastest		
Video BIOS Cacheable	: Enabled		
System BIOS Cacheable	: Enabled		
Memory Hole at 15M-16M	: Disabled		

PNP/PCI Configuration

PNP OS Installed	: No	CPU to PCI Write Buffer	: Enabled
Resources Controlled By	: Auto	PCI Dynamic Bursting	: Enabled
Reset Configuration Data	: Disabled	PCI Master 0 WS Write	: Enabled
		PCI Peer Concurrency	: Disabled
		PCI Delay Tranaction	: Disabled
		PCI IRQ Activd By	: Level
		PCI IDE IRQ Map To PCI	: PCI-Auto
		Primary IDE INT#	: A
		Secondary IDE INT#	: B

Integrated Peripherals

OnChip IDE First Channel	: Enabled
OnChip IDE Second Channel	: Enabled
IDE Prefetch Mode	: Enabled
IDE HDD Block Mode	: Disabled Enabled
IDE Primary Master PIO	: Auto
IDE Primary Slave PIO	: Auto
IDE Secondary Master PIO	: Auto
IDE Secondary Slave PIO	: Auto
IDE Primary Master UDMA	: Auto
IDE Primary Slave UDMA	: Auto
IDE Secondary Master UDMA	: Auto
IDE Secondary Slave UDMA	: Auto
OnBoard FDD Controller	: Enabled
OnBoard UART Port 1	: 3F8/IRQ4
OnBoard UART Port 2	: Disabled
OnBoard Parallel Port	: 378/IRQ7
Parallel Port Mode	: Normal