

Award Bios Setup (2A59IIR09) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User				0			Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----
Drive A	: None							
Drive B	: 1.44M, 3.5 in.							
Video	: EGA/VGA							
Halt On	: All Errors							

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF shadow	: Disabled
		D0000-D3FFF Shadow	: Disabled
Quick Power On Self Test	: Enabled	D4000-D7FFF Shadow	: Disabled
Boot Sequence	: C only	D8000-DBFFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up Floppy Drive	: Disabled		
Boot up Num Lock	: On		
Boot up System Speed	: High		
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Rate (Msec)	: 250		
Security Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		
OS Select For DRAM > 64 MB	: Non-OS2		
Report No FDD for WIN 95	: No		

CHIPSET FEATURES SETUP

Auto Configuration	: Disable	CPU to PCI Post Write	: 3T
		CPU to PCI Burst Mem. WR	: Disabled
L2 (WB) Tag Bit Length	: 8 Bits	ISA Bus Clock Frequency	: PCICLK/4
SRAM Back-to-Back	: Enabled	System BIOS Cacheable	: Enabled
NA# Enable	: Enabled	Video BIOS Cacheable	: Enabled
Starting Point of Paging	: 1T	Memory Hole at 15M-16M	: Disabled
Refresh Cycle Time (us)	: 187.2		
RAS Pulse Width Refresh	: 6T		
RAS Precharge Time	: 4T		
RAS to CAS Delay	: 4T		
CAS# Pulse Width (FP)	: 2T		
CAS# Pulse Width (EDO)	: 1T		
CAS Precharge Time (FP)	: 1T/2T		
CAS Precharge Tiime (EDO)	: 1T/2T		
SDRAM CAS Latency	: 3T		
SDRAM WR Retire Rate	: X-2-2-2		
SDRAM Wait State Control	: 1WS		
Read Prefetch Memory RD	: Enabled		

PNP/PCI Configuration

Resources Controlled By	: Auto	PCI IRQ Activated By	: Level
Reset Configuration Data	: Disabled	PCI IDE 2nd Channel	: Enabled
		PCI IDE IRQ Map To	: PCI Auto
		Primary IDE INT #	: A
		Secondary IDE INT #	: B

Integrated Peripherals

Internal PCI/IDE	: Both	OnBoard Parallel Mode	: SPP
IDE Primary Master PIO	: Auto		
IDE Primary Slave PIO	: Auto		
IDE Secondary Master PIO	: Auto		
IDE Secondary Slave PIO	: Auto	PS/2 mouse function	: Disabled
Primary Master UltraDMA	: Auto	USB Controller	: Disabled
Primary Slave UltraDMA	: Auto		
Secondary Master UltraDMA	: Auto		
Secondary Slave UltraDMA	: Auto		
IDE Burst Mode	: Enabled		
IDE Data Port Post Write	: Enabled		
IDE HDD Block Mode	: Disabled		
OnBoard FDD Controller	: Enabled		
OnBoard Serial Port 1	: 3F8/IRQ4		
OnBoard Serial Port 2	: Disabled		
OnBoard Parallel Port	: 378/IRQ7		