

Award Bios Setup (2A59IA1F) PCI Pentium

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: Auto	0	0	0	0	0	0	Auto
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----

Drive A : None
Drive B : 1.44M, 3.5 in.
Floppy 3 Mode Support : Disabled
Video : EGA/VGA
Halt On : All Errors

CPU SOFT MENU

CPU Name is	: AMD K6	CPU Power Plane	: Dual
CPU Operating Speed is	: 200	I/O Plane Voltage	: 3.30V 3.38V
Turbo	: Disabled	Core Plane Voltage	: 2.90V

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF shadow	: Disabled
Quick Power On Self Test	: Enabled	D0000-D3FFF Shadow	: Disabled
Boot Sequence	: C,A,SCSI	D4000-D7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	D8000-DBFFF Shadow	: Disabled
Boot up Floppy Drive	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up Num Lock	: On		
IDE HDD Block Mode	: Disabled		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay (Msec)	: 250		
Security Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		
OS Select For DRAM > 64 MB	: Non-OS2		
Report No FDD for WIN 95	: No		
Delay IDE Inital	: 0		

CHIPSET FEATURES SETUP

Auto Configuration	: Disable		
DRAM Leadoff Timing	: 10 / 6 / 4	10 / 6 / 3	
DRAM Read Burst (EDO/FP)	: x333 / x444	x222 / x333	
DRAM Write Burst Timing	: x333	x222	
Fast EDO Lead Off	: Disabled	Enabled	
Refresh RAS# Assertion	: 5 CLKS	4 CLKS	
Fast RAS to CAS Delay	: 3	2	
DRAM Page Idle Timer	: 2 CLKS		
DRAM Enhanced Paging	: Enabled		
Fast MA to RAS # Delay	: 2 CLKS		
SDRAM (CAS Lat/RAS-to-CAS)	: 3/3		
SDRAM Speculative Read	: Disabled		
System BIOS Cacheable	: Enabled	Disabled	
Video BIOS Cacheable	: Enabled		
8 Bit I/O Recovery Time	: 1		
16 Bit I/O Recovery Time	: 2		
Memory Hole at 15M-16M	: Disabled		
PCI 2.1 Compliance	: Enable		

PCI & OnBoard I/O Setup

Force Update ESCD	: Disabled
BIOS Auto-Config PCI IRQ	: Enabled
PCI IRQ Activated By	: Level
Assign IRQ for PCI VGA	: Auto
PCI IDE Card 2 nd Channel	: Enabled
PCI IDE Card IRQ Map to	: PCI-AUTO
- Primary IDE Int#	: A
- Secondary IDE Int#	: B
USB KeyBoard Support Via	: OS
OnBoard IDE-1 Controller	: Enabled
Master Drive PIO Mode	: Auto
Slave Drive PIO Mode	: Auto
OnBoard IDE-2 Controller	: Disabled
OnBoard UBS Assigned IRQ	: Disabled
OnBoard FDD Controller	: Enabled
OnBoard Serial Port 1	: 3F8/IRQ4
OnBoard Serial Port 2	: Disabled
OnBoard Parallel Port	: 378/IRQ7
ParallelPort Mode	: SPP