

Award Bios Setup (2A5LEF09)

HARD DISKS	TYPE	SIZE	CYLS	HEAD	PRECOMP	LANDZ	SECTOR	MODE
Primary Master	: User							Normal
Primary Slave	: None	0	0	0	0	0	0	-----
Secondary Master	: None	0	0	0	0	0	0	-----
Secondary Slave	: None	0	0	0	0	0	0	-----
Drive A	: None							
Drive B	: 1.44M, 3.5 in.							
Video	: EGA/VGA							
Halt On	: All Errors							

BIOS FEATURES SETUP

Virus Warning	: Disabled	Video BIOS Shadow	: Enabled
Detect Boot Virus by Trend	: Disabled		
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF shadow	: Disabled
Quick Power On Self Test	: Enabled	D0000-D3FFF Shadow	: Disabled
Boot from LAN first	: Disabled		
Boot Sequence	: C only	D4000-D7FFF Shadow	: Disabled
		D8000-DBFFF Shadow	: Disabled
Boot up Floppy Drive	: Disabled	DC000-DFFFF Shadow	: Disabled
Boot up NumLock Status	: On		
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Rate (Msec)	: 250		
Security Option	: Setup		
OS Select For DRAM > 64 MB	: Non-OS2		

CHIPSET FEATURES SETUP

Video BIOS Cacheable	: Enabled
System BIOS Cacheable	: Enabled
Memory Hole at 15M-16M	: Disabled
DRAM Page Mode	: Enable
Sustained 3t Write	: Enable
Write Cache Pipeline	: Enabled
DRAM Read Pipeline	: Enable
Read Around Write	: Disable
Memory ECC Check	: Disable
Bank 0/1 DRAM Timing	: Normal
Bank 2/3 DRAM Timing	: Normal
Bank 4/5 DRAM Timing	: Normal
SDRAM Cycle Length	: 3
SDRAM Banl Interleave	: Disable
SDRAM MB to HD POP+1t	: Disable
SDRAM Sustain 4t Cycle	: Enable
AGP Aperture Size (MB)	: 4Meg
AGP-2X Mode	: Disable
Spread Spectrum Modulation	: Enable

PNP/PCI Configuration

PNP OS Installed	: No	PCI IRQ Activated By	: Level
Resources Controlled By	: Auto	Assign IRQ For VGA	: Enabled
Reset Configuration Data	: Disabled	PCI Slot 1 Use IRQ	: Auto
		PCI Slot 2 Use IRQ	: Auto
		PCI Slot 3 Use IRQ	: Auto
		PCI Slot 4 Use IRQ	: Auto

Integrated Peripherals

IDE HDD Block Mode	: Disabled	Onboard FDC Controller	: Enabled
Onchip Primary PCI IDE	: Enabled	OnBoard UART 1	: 3F8/ IRQ 4
Onchip Secondary PCI IDE	: Disabled	OnBoard UART 2	: Disabled
IDE Primary Master PIO	: Auto	OnBoard Parallell Port	: 378/ IRQ 7
IDE Primary Slave PIO	: Auto	Parallell Port mode	: ECP + EPP
IDE Primary Master UDMA	: Auto	ECP Mode Use DMA	: 3
IDE Primary Slave UDMA	: Auto	Parallell Port EPP Type	: 1.9
HDD S.M.A.R.T. Capability	: Disabled		
USB Controller	: Disabled		
Init Display First	: PCI Slot		