

## Award Bios Setup (2A5LED4C)

| HARD DISKS       | TYPE   | SIZE | CYLS | HEAD | PRECOMP | LANDZ | SECTOR | MODE  |
|------------------|--------|------|------|------|---------|-------|--------|-------|
| Primary Master   | : Auto | 0    | 0    | 0    | 0       | 0     | 0      | Auto  |
| Primary Slave    | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |
| Secondary Master | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |
| Secondary Slave  | : None | 0    | 0    | 0    | 0       | 0     | 0      | ----- |

Drive A : None  
Drive B : 1.44M, 3.5 in.

Video : EGA/VGA  
Halt On : All Errors

## BIOS FEATURES SETUP

|                            |            |                    |            |
|----------------------------|------------|--------------------|------------|
| Virus Warning              | : Disabled | Video BIOS Shadow  | : Enabled  |
| CPU Internal Cache         | : Enabled  | C8000-CBFFF Shadow | : Disabled |
| External Cache             | : Enabled  | CC000-CFFFF shadow | : Disabled |
| Quick Power On Self Test   | : Enabled  | D0000-D3FFF Shadow | : Disabled |
| Boot Sequence              | : C only   | D4000-D7FFF Shadow | : Disabled |
| Swap Floppy Drive          | : Disabled | D8000-DBFFF Shadow | : Disabled |
| Boot up Floppy Drive       | : Disabled | DC000-DFFFF Shadow | : Disabled |
| Boot up NumLock Status     | : On       |                    |            |
| Memory FCC Function        | : Disabled |                    |            |
| Typematic Rate Setting     | : Disabled |                    |            |
| Typematic Rate (Chars/Sec) | : 6        |                    |            |
| Typematic Rate ( Msec)     | : 250      |                    |            |
| Security Option            | : Setup    |                    |            |
| PCI/VGA Palette Snoop      | : Enabled  |                    |            |
| OS Select For DRAM > 64 MB | : Non-OS2  |                    |            |
| HDD S.M.A.R.T. Capability  | : Enabled  |                    |            |

## CHIPSET FEATURES SETUP

|                          |            |                       |                    |
|--------------------------|------------|-----------------------|--------------------|
| DIMM 1 DRAM Timing       | : Normal   | System Health Monitor | : Ignore all below |
| DIMM 2 DRAM Timing       | : Normal   |                       |                    |
| DIMM 3 DRAM Timing       | : Normal   |                       |                    |
| SDRAM CAS Latency        | : 3        |                       |                    |
| SDRAM Bank Interleave    | : Disabled |                       |                    |
| Video BIOS Cacheable     | : Enabled  |                       |                    |
| System BIOS Cacheable    | : Enabled  |                       |                    |
| Memory Hole at 15M - 16M | : Disabled |                       |                    |
| AGP Aperture Size (MB)   | : 4        |                       |                    |
| AGP-2X Mode              | : Disabled |                       |                    |
| CPU to PCI Write Buffer  | : Enabled  |                       |                    |
| PCI Dynamic Bursting     | : Disabled |                       |                    |
| PCI Mater 0 WS Write     | : Disabled |                       |                    |
| PCI Delay Transaction    | : Disabled |                       |                    |
| PCI Master Read Prefetch | : Disabled |                       |                    |
| PCI #2 Access #1 Retry   | : Disabled |                       |                    |
| AGP Master 1 WS Write    | : Disabled |                       |                    |
| AGP Master 1 WS Read     | : Disabled |                       |                    |

## PNP/PCI Configuration

|                          |            |                      |           |
|--------------------------|------------|----------------------|-----------|
| Resources Controlled By  | : Auto     | PCI IRQ Activated By | : Level   |
| Reset Configuration Data | : Disabled | Assign IRQ For VGA   | : Enabled |
|                          |            | PCI Slot 1 Use IRQ   | : Auto    |
|                          |            | PCI Slot 2 Use IRQ   | : Auto    |
|                          |            | PCI Slot 3 Use IRQ   | : Auto    |
|                          |            | PCI Slot 4 Use IRQ   | : Auto    |

## Integrated Peripherals

|                           |            |                        |             |
|---------------------------|------------|------------------------|-------------|
| Onboard Primary PCI IDE   | : Enabled  | Onboard FDC Controller | : Enabled   |
| Onboard Secondary PCI IDE | : Disabled | Onboard UART1          | : 3F8/ IRQ4 |
| IDE Prefetch Mode         | : Enabled  | Onboard UART2          | : Disabled  |
| IDE HDD Block Mode        | : Enabled  |                        |             |
| IDE Primary Master PIO    | : Auto     |                        |             |
| IDE Primary Slave PIO     | : Auto     | Onboard Parallel Port  | : 378/ IRQ7 |
|                           |            | Parallel Port Mode     | : ECP + EPP |
| IDE Primary Master UDMA   | : Auto     | ECP Mode Use DMA       | : 3         |
| IDE Primary Slave UDMA    | : Auto     | Parallel Port EPP Type | : EPP1.7    |

USB Controller : Disabled

Init Display First : PCI Slot